

CTSCT004.2

Citroen Steering Wheel Control Interface





Vehicle Application

Citroen C2 2005 - 2009 Citroen C3 (Pluriel, H) 2005 - 2016 Citroen C4 (L) 2004 - 2010 Citroen C5 (1DC/DE) 2005 - 2008 Citroen C8 2005 - 2014

For Open Dash Vehicles Only

Key Features

Retains Steering Wheel Controls (if equipped)
Provides Speed Pulse, Park Brake, Reverse Gear & Illumination





The information provided in this document is subject to change without notice due to changes and/or improvements to the product/s.

ABOUT THIS PRODUCT

CTSCT004.2

CAN-Bus Steering Wheel Control Interface for Citroen Vehicles with Open Dash and 40 Pin Quadlock Connector.

WIRING COLOUR CODES

Purple	Right Rear Speaker +	Yellow	Permanent 12V
Purple/Black	Right Rear Speaker -	Black	Ground
Green	Left Rear Speaker +	Red	Ignition 12V
Green/Black	Left Rear Speaker -	Orange	Illumination
Grey/Black	Right Front Speaker +	Pink	Speed Pulse
White	Right Front Speaker -	Green	Park Brake
White (Black	Left Front Speaker +	Purple/White	Reverse Gear
White/Black	Left Front Speaker -		

PRIOR TO INSTALLATION

Read the manual prior to installation. Technical knowledge is necessary for installation. The place of installation must be free of moisture and away from heat sources. Please ensure that the correct tools are using during the installation to avoid damage to the vehicle or product. **Connects2 can not be held responsible for the installation of this product.**

TECHNICAL SUPPORT

Connects2 Ltd. want to provide a fast and suitable resolution to any problems encountered during installation of this product. To get in touch with our dedicated technical support team, please fill in a ticket at **support.connects2.com** and provide as much information as possible.



FITTING GUIDE

1. Remove and disconnect the original head unit.

2. Connect the 12 way molex connector of the head unit patch lead (supplied separately) to the interface.





3. Connect the opposite end of head unit patch lead to the head unit steering wheel control input on the back of the aftermarket head unit.

NB: This may be a 3.5mm jack plug or a wire input depending upon the head unit brand being fitted. Please see the head unit installation manual for further information on where to connect.

Important: This step must be completed before connecting power to the interface. Failure to so do may result in no steering wheel control function.



4. Connect the 14 way molex connector to the interface





5. Connect the male power/speaker ISO harness to the female power/speaker ISO harness from the aftermarket head unit. For aftermarket head units without an ISO connector, please refer to "Wiring Colour Codes" on Pg. 2.



www.connects2.com

FITTING GUIDE

6. Connect the female vehicle specific connectors on the harness to the male vehicle connector from the vehicle. Test head unit for correct operation.

Original Button	Function
Scroll Wheel	Volume +
Scroll Wheel	Volume -
Track +	Track +
Track -	Track -
SRC	Source

STEERING WHEEL CONTROL FUNCTIONALITY